

# FC632 Optical Fiber -Optical Transceiver Product Specification

- FC632 a e de e c e ca a ee e .
- O e e e ace, e ca be e ace, a d e ca be - ca e ace a e SC c ec .
- DC 5V e , e e a d a ce ca eac 20K .
- M de J ca be a e 8.3/125, 8.7/125, 9/125 10/125 .
- 10/100M/1000Mb -d e / a -d e a a c e a .
- B - e c e c c c e, e b adca ,ac e e c ,CRC e c ec .
- S SPANNING TREE c c a - e a e .
- C a ce: IEEE802.3Z/AB 1000Ba e-T/SX/LX a da d.
- C a ce: IEEE802.3Z/AB 1000Ba e-T/SX/LX a da d.
- Ne Cab e 10/100/1000Ba e-TX UTP 5E, 6 ca e e .
- Mee e EUR HS a da d.
- Pa 3C, CE, FCC ce ca .



I d ca	c	S a e	W a
PWR	P e I d ca La	L	P e
		NOT SHINY	N e
FDX	L P L S a I d ca	L	C ec
		NOT SHINY	N c ec
FX/ACT	L P L S a I d ca	L	C ec
		F a	Da a
		NOT SHINY	N c ec
TP/ACT	L P L S a I d ca	L	C ec
		F a	Da a
		NOT SHINY	N c ec ed
1000M	Ne P S a I d ca	L	1000M a
100M	Ne P S a I d ca	L	100M a

#### 4

P d c a a e e	
T e	S e de e c e
P e	DC5V
Ne a e	10/100/1000Mb e -ada
O ca F be T a Ra e	1000Mb
O ca be e ace	SC e ace
E ec ca e ace	RJ45
a d a ce	20
S e	140 110 30 (Le , d a d e )
a b e e e a e	0 50
S a e e e a e	-20 70

